


1002 1480 nm Pump

PL-1425-PM-320



1425 nm Pump Laser Diode, 320 mW, PM Fiber

The pump has been designed for use in a wide variety of optical amplifiers, such as EDFA and Raman amplifiers used in optical transmission systems, especially in dense wavelength division multiplexing (DWDM) systems. A strained multi-quantum well (st-MQW) laser diode chip is integrated with thermo-electric cooler (TEC) and PIN photodiode in a hermetically sealed 14-pin butterfly package.


FEATURES

- Rated Output Power up to 320 mW (CW)
- Widely Deployed Reliable Package Design with Industry Compatible 14 Pin Butterfly Footprint
- Internal Thermo-electric Cooler (TEC) and Thermistor For Stable Operation
- Integrated Pin Photodiode for Back Facet Monitor
- Single Mode Fiber and Polarization Maintaining Fiber Pigtail
- Epoxy Free Design Inside the Module for Long Term Reliability

USE IN

- Pump Source for Er-Doped Fiber Amplifier
- C- and/or L-band EDFA
- Single Channel Amp. to DWDM Amp.
- Pump Source for Raman Amplifier

FUNCTIONAL DIAGRAM



Pin Description	
1	Cooler (+)
2	Thermistor
3	PD Anode (-)
4	PD Cathode (+)
5	Thermistor
6	Not Connected
7	Not Connected

Pin Description	
8	Not Connected
9	Not Connected
10	LD Anode (+)
11	LD Cathode (-)
12	Not Connected
13	Case GND
14	Cooler (-)

Order notes to our customers: The default parameters are as follows. For special needs, please contact sales.

1) Connector FC/APC, 900 um, 1 m by default for all devices except for high power devices.

2) Slow axis working, fast axis blocked, connector key is aligned to slow axis by default for PM devices.

1002 1480 nm Pump

PL-1425-PM-320


Storage Temperature	-40°C to 85°C
Operation Temperature	-20°C to 70°C
LD Forward Current	1600 mA max.
LD Reverse Voltage	2 V max.
PD Forward Current	5 mA max.
PD Reverse Voltage	20 V max.
TEC Current	-1.1 A min.; 4.5 A max.
TEC Voltage	4.5 V max.
Output Power	320 mW
Center Wavelength (FP)	1460 nm to 1490 nm
Center Wavelength (FBG)	1420 nm to 1510 nm (± 1.5 nm)
Spectral Width (FP)	8 nm max.
Spectral Width (FBG)	3 nm max.
LD Forward Voltage	2.6 V max.
LD Forward Current at EOL	1.2xI _{fBOL} mA max.
Monitor Current	100 μ A min.; 2000 μ A max.
Monitor Dark Current	100 nA max.
Extinction Ratio	16 dB min. (Type 4 & Type 6)
Isolation	30 dB min. (Type 3 & Type 4)
Thermistor Resistance	9.5 k Ω min.; 10 k Ω typ.; 10.5 k Ω max.
Thermistor B Constant	3900 typ.

Order notes to our customers: The default parameters are as follows. For special needs, please contact sales.
1) Connector FC/APC, 900 μ m, 1 m by default for all devices except for high power devices.
2) Slow axis working, fast axis blocked, connector key is aligned to slow axis by default for PM devices.

1002 1480 nm Pump

PL-1425-PM-320

MECHANICAL DRAWING



Type 3: SMF Pigtail w/Isolator

Type 4: PMF Pigtail w/Isolator

Type 6: PMF Pigtail w/FBG

Order notes to our customers: The default parameters are as follows. For special needs, please contact sales.

- 1) Connector FC/APC, 900 um, 1 m by default for all devices except for high power devices.
- 2) Slow axis working, fast axis blocked, connector key is aligned to slow axis by default for PM devices.