

DMLT-1550-SR



DM Transmitter - Short Reach

The QAMnet DMLT-1550-SR series laser transmitters are reliable and cost-effective for HFC, RFoG, FTTH and deep fiber applications. The DMLT-1550-SR uses a highly linear DFB laser module and an advanced predistortion RF drive circuit to deliver 50 dB of CNR, while maintaining optimal CSO and CTB distortion specifications.

The DMLT-1550-SR has a standard transmission range of 10 km. Since the transmitter operates at 1550 nm wavelength, the output signal can be easily amplified by an EDFA to extend the transmission range. The DMLT-1550-SR transmitters support up to 75 NTSC analog channels and since they are designed to be digitally ready, they can be loaded with 60 additional QAM modulated signal channels. The DMLT-1550-SR is available with three output power levels: +6 dBm, +8 dBm and +10 dBm.

Features

- Highly linear, analog-modulated 1550 nm DFB laser source
- Advanced pre-distortion circuit minimizes CSO and CTB distortion
- Optional Automatic Gain Control (AGC) for optimal RF drive level
- 75 channel NTSC plus 60 digital channels loading plan
- -20 dB front panel RF test port
- 45 MHz to 870 MHz modulation bandwidth

Applications

- HFC
- FTTH
- RFoG
- Deep Fiber Applications

DM Transmitter - Short Reach

OPTIONS

DMLT-1550-SR-xx-y
xx Output power level +6 to +10 dBm
y a (Without AGC); b (With AGC)

TECHNICAL INFO

For technical info and support:

sales@optilab.com

www.optilab.com

WEB ORDER

To order, please click below.



Optilab Advantage

- Innovation
- Performance
- Quality
- Customization
- Warranty

Optical Specifications	
Laser Wavelength Range	1550 nm ± 15 nm, Specific Wavelength on ITU Grid optional
Transmission Range	Up to 10 km in SMF-28 fiber
Output Power Level	6.0 dBm typ. (5.7 dBm (min.)), 8.0 dBm typ. (7.7 dBm min.), 10 dBm typ. (9.7 dBm min.)
Number of Outputs	1
Optical Return Loss	50 dB min.
Carrier to Noise Ratio (CNR)	52 dB typ. @ 0dBm
Composite Second Order (CSO) Distortion	-60 dBc max.
Composite Triple Beat (CTB) Distortion	-62 dBc max.
RF Test Port Ratio	-20 dB
AGC Adjustment Range	6 dB (optional)
Input RF Power Level	13 to 18 dBmV per channel
Frequency Range	45 MHz to 870 MHz
Flatness in Frequency Range	±0.75 dB
Input Impedance	75 Ω
Input RF Return Loss	16 dB min.

Mechanical Specifications	
Temperature Range	0°C to +50°C (operation)
Temperature Range	-40°C to +70° C (storage)
Power Supply	80 – 240 V, 43 – 63 Hz AC 40 - 58 VDC (optional)
Power Consumption	30 W max.
Housing Dimensions	1U Rack: 19"(W) x 14"(D) x 1.75"(H)
Control / Monitoring	DFB Laser Temperature and Current,
Display	Output Power Level, TEC temperature
Alarm	Over Temperature , Over Current
Optical Connectors	SC/APC or Customer Specified